

**Amendment to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

Claim 1 (currently amended): A method for operating a point-to-multipoint wireless communication network, said method comprising:

measuring link delays between a root bridge and a plurality of non-root bridges;  
and

using said measured link delays to coordinate transmissions in a CSMA/CA scheme, wherein using comprises calculating a common time slot value based on said measured link delays and distributing said measured link delays and said common time slot value within said point-to-multipoint wireless communication network; and

aligning contention timing boundaries based on said measured link delays and said common time slot values.

Claim 2 (canceled).

Claim 3 (canceled).

Claim 4 (canceled).

Claim 5 (original): The method of claim 1 wherein measuring and using are performed by said root bridge.

Claim 6 (original): The method of claim 1 wherein measuring and using are performed by one of said non-root bridges.

Claim 7 (original): The method of claim 1 wherein using comprises:  
assigning transmission deferral times to said non-root bridges based on said measured link delays to give access preference to more distant ones of said non-root bridges.

Claim 8 (currently amended): A method for operating a node in a point-to-multipoint wireless communication network, said method comprising:

receiving a measured link delay and a system slot time from another node, said system slot time calculated based on said measured link delay; and

using said measured link delay and said system slot time to coordinate transmissions in a CSMA/CA scheme;

wherein contention timing boundaries are aligned based on said measured link delay and said common slot time.

Claim 9 (currently amended): A method for operating a point-to-multipoint wireless communication network, said method comprising:

measuring link delays between an access point and a plurality of stations; and

using said measured link delays to coordinate transmissions in a CSMA/CA scheme, wherein using comprises calculating a common time slot value based on said measured link delays and distributing said measured link delays and said common time slot value within said point-to-multipoint wireless communication network; and

aligning contention timing boundaries based on said measured link delays and said common time slot values.

Claim 10 (currently amended): Apparatus for operating a node in a point-to-multipoint wireless communication network, said apparatus comprising:

a link delay counter that measures delays between a root bridge and a plurality of non-root bridges; and

a MAC processor that calculates a common time slot value based on said measured link delay, distributes said measured link delays and said common time slot value within said point-to-multipoint wireless communication network, uses said measured link delays to coordinate transmissions in a CSMA/CA scheme, and aligns contention timing boundaries based on said measured link delays and said common time slot values.

Claim 11 (canceled).

Claim 12 (canceled).

Claim 13 (canceled).

Claim 14 (original): The apparatus of claim 10 wherein said node is said root bridge.

Claim 15 (original): The apparatus of claim 10 wherein said node is one of said non-root bridges.

Claim 16 (original): The apparatus of claim 10 wherein said MAC layer processor assigns transmission deferral times to said non-root bridges based on said measured link delays to give access preference to more distant ones of said non-root bridges.

Claim 17 (currently amended): Apparatus for operating a node in a point-to-multipoint wireless communication network, said apparatus comprising:

a physical layer block that receives a measured link delay and a system slot time from another node, said system slot time calculated based on said measured link delay; and

a MAC layer processor that uses said measured link delay and said system slot time to coordinate transmissions in a CSMA/CA scheme;

wherein contention timing boundaries are aligned based on said measured link delay and said common slot time.

Claim 18 (currently amended): Apparatus for operating a point-to-multipoint wireless communication network, said apparatus comprising:

a link delay counter that measures link delays between an access point and a plurality of stations; and

a MAC layer processor that calculates a common time slot value based on said measured link delay, distributes said measured link delays and said common time slot value within said point-to-multipoint wireless communication network, uses said measured link delays to coordinate transmissions in a CSMA/CA scheme, and aligns contention timing boundaries based on said measured link delays and said common time slot values.

Claim 19 (currently amended): Apparatus for operating a point-to-multipoint wireless communication network, said apparatus comprising:

means for measuring link delays between a root bridge and a plurality of non-root bridges;~~and~~

means for using said measured link delays to coordinate transmissions in a CSMA/CA scheme, wherein means for using comprises means for calculating a common time slot value based on said measured link delays and distributing said measured link delays and said common time slot value within said point-to-multipoint wireless communication network; and

means for aligning contention timing boundaries based on said measured link delays and said common time slot values.

Claim 20 (currently amended): A computer-readable medium storing computer executable instructions for operating a point-to-multipoint wireless communication network, said instructions comprising:

code that causes measurement of said link delays between a root bridge and a plurality of non-root bridges;~~and~~

code that causes use of said measured link delays to coordinate transmissions in a CSMA/CA scheme, wherein said measured link delays is used in calculating a common time slot value based on said measured link delays and distributed along with said common time slot value within said point-to-multipoint wireless communication network; and

code that causes alignment of contention timing boundaries based on said measured link delays and said common time slot values.

Claim 21 (previously presented): The method of claim 1 wherein coordinating transmissions comprises adjusting a network allocation vector time.